

## TETENAL Red Sensitive Film

**TETENAL Red Sensitive Film** is a high quality image setting film with a spectral density between 630 and 780 nm.

**TETENAL Red Sensitive Film** can be used in a lot of image setters.

**TETENAL Red Sensitive Film** will be developed with **TETENAL Reproline Special** and **TETENAL Repro Superfix Special**.

### TETENAL Red Sensitive Film DS-HN

Packaging size = 1 roll / Price only on quotation.

Format	Light Source	Loading Spec.	Art.-No.
338 mm x 60 m	HN/RLD-A	829	105700
355 mm x 60 m	HN/RLD-A	829	105715
406 mm x 60 m	HN/RLD-A	989 R	105706
508 mm x 60 m	HN/RLD-A	390 R	105703
520 mm x 60 m	HN/RLD-A	989	105704
550 mm x 60 m	HN/RLD-A	989	105702
559 mm x 60 m	HN/RLD-A	989 R	105708
600 mm x 60 m	HN/RLD-A	829	105701
762 mm x 60 m	HN/RLD-A	829	105705
762 mm x 60 m	HN/RLD-A	989 R	105708
762 mm x 60 m	HN/RLD-A	989	105711
838 mm x 60 m	HN/RLD-A	390 R	105710
914 mm x 60 m	HN/RLD-A	829	105716

Format	Light Source	Loading Spec.	Art.-No.
338 mm x 60 m	IR-A	829	105712
338 mm x 30 m	IR-A	867	105713

### TETENAL Red Sensitive Film HN/RLD-A MATT

Packaging size = 1 roll / Price only on quotation.

Format	Light Source	Loading Spec.	Art.-No.
338 mm x 60 m	HN/RLD-A Matt	829	105740
355 mm x 60 m	HN/RLD-A Matt	829 R	105714
762 mm x 60 m	HN/RLD-A Matt	989	105742

## TETENAL Red Sensitive Film

**TETENAL Red Sensitive Film** is a high quality image setting film with a spectral density between 630 and 780 nm.

**TETENAL Red Sensitive Film** can be used in a lot of image setters.

**TETENAL Red Sensitive Film** will be developed with **TETENAL Reproline Special** and **TETENAL Repro Superfix Special**.

### TETENAL Red Sensitive Film HN/RLD-S und IR-S

Packaging size = 1 roll / Price only on quotation.

Format	Light Source	Loading Spec.	Art.-No.
338 mm x 60 m	HN/RLD-S	829	105762
356 mm x 60 m	HN/RLD-S	829	105751
406 mm x 60 m	HN/RLD-S	989 R	105756
457 mm x 60 m	HN/RLD-S	829	105763
459 mm x 60 m	HN/RLD-S	989	105780
460 mm x 60 m	HN/RLD-S	829	105777
508 mm x 60 m	HN/RLD-S	390 R	105753
520 mm x 60 m	HN/RLD-S	989	105754
520 mm x 60 m	HN/RLD-S	829	105776
549 mm x 60 m	HN/RLD-S	989	105781
550 mm x 60 m	HN/RLD-S	989	105752
558 mm x 60 m	HN/RLD-S	829	105765
559 mm x 60 m	HN/RLD-S	989 R	105757
610 mm x 60 m	HN/RLD-S	989 R	105778
660 mm x 60 m	HN/RLD-S	829	105779
724 mm x 60 m	HN/RLD-S	829	105766
762 mm x 60 m	HN/RLD-S	829	105755
762 mm x 60 m	HN/RLD-S	989	105759
762 mm x 60 m	HN/RLD-S	989 R	105760
785 mm x 60 m	HN/RLD-S	390 R	105783
838 mm x 60 m	HN/RLD-S	390 R	105758
914 mm x 60 m	HN/RLD-S	829	105767

Format	Light Source	Loading Spec.	Art.-No.
338 mm x 30 m	IR-S	829	105761
355 mm x 60 m	IR-S	829	105773
460 mm x 60 m	IR-S	829	105782

Min. order qty: 10 rolls